

RoHS (Restriction of Hazardous Substances)

Certificate of Compliance

MKS Instruments, Inc. hereby certifies that the products listed in the attached table are compliant with the European Union's RoHS directive 2011/65/EU (effective 22 July 2021) regarding the restriction of the use of certain hazardous substances in electrical and electronic equipment. The products listed below are compliant to RoHS requirements for concentration limitations, by weight of homogeneous material, of the ten substances shown on the following page.

Product

Photonics Business Unit

RoHS Compliant Part Number

Adjustment Screw, Tiny Knob, 9.6 mm 9345 Travel, Ball Tip, 6-80

The above thresholds are not in place for any legally allowable exemptions per Annex III of the aforementioned directive. If such exemptions are in use, they are noted on the attached table. If no exemptions are in use, then no further information is provided.

All information provided in this Certificate of Compliance is accurate to MKS' knowledge as of the date of this certification. This confirmation is made based our internal engineering risk analysis of the individual items possibly being present along with the best technical information made available to MKS from its material suppliers.

Gwen Briens

Date

Vice-President and General Manager

MKS Instruments, Inc. Page 1 of 2 Document Number: MKS-CD-1459

MKS CONFIDENTIAL Revision: B

LIST OF SUBSTANCES BANNED BY ROHS2 – JULY 2021

(Item cannot exceed 0.1% of homogeneous material – except as noted)

- o Lead (Pb)
- o Mercury (Hg)
- Cadmium (Cd) 0.01% limit
- O Hexavalent chromium (Cr6+)
- o Polybrominated biphenyls (PBB)
- o Polybrominated diphenyl ether (PBDE)
- o Diisobutyl phthalate (DIBP)
- o Bis (2-ethylhexyl) phthalate (DEHP)
- o Butyl benzyl phthalate (BBP)
- o Dibutylphthalate (DBP)

MKS RoHS2 PRODUCT EXEMPTION LISTING

MKS Product	MKS Product	Annex III	Annex III
Number	Description	Exemption #	Exemption Description
9345	Adjustment	A3, 6(C)	Lead
	Screw, Tiny		
	Knob, 9.6 mm		
	Travel, Ball Tip,		
	6-80		